

- Trinnløs justerbar utgangsspenning
- Sekundærsvitsjet
- Termosikring i transformator
- Nettledning
- Sekundærledning eller snappkontakt
- Kan leveres med festebrakett
- *Stepless adjustable output voltage*
- *Secondary switch*
- *Thermal fuse in transformer*
- *Mains cord*
- *Cable or snap terminals*
- *Mounting bracket available*

**Tekniske data****Technical specifications**

Inngangsspenning:	<i>Input voltage:</i>	230 VAC +6/-10%, 50/60Hz
Utgangsspenning:	<i>Output voltage:</i>	5-24 VDC
Maks. utgangseffekt:	<i>Max. output power:</i>	18 W
Maks. laststrøm	<i>Max. load current:</i>	2,0 A
Lastregulering:	<i>Load regulation:</i>	2,0%
Linjeregulering:	<i>Line regulation:</i>	0,1%
Svitsjefrekvens:	<i>Switch frequency:</i>	33 kHz
Temperaturområde:	<i>Temperature range:</i>	-10°C - +40°C
Rippel:	<i>Ripple:</i>	10 mV RMS
Strømbegrensning:	<i>Current limiting:</i>	2,5 A *
Isolasjonsklasse:	<i>Insulation class:</i>	II
Isolasjonsspenning:	<i>Insulation voltage:</i>	3000 VAC
Elektrisk sikkerhetsstandard:	<i>Electrical safety standard:</i>	EN 60065, EN 60950
EMC standarder	<i>EMC standards</i>	
• Emisjon:	• <i>Emission:</i>	EN 61000-6-3, EN 60555
• Immunitet:	• <i>Immunity:</i>	EN 61000-6-1
Mål (LxBxH):	<i>Dimensions (LxWxH):</i>	98 x 108 x 55 mm
Vekt:	<i>Weight:</i>	1,0 kg

* Strømbegrensning er innvendig justerbar.

* *Current limiting is internally adjustable.*